

Product Information

Self adhesive PVC film with a reflection free, matt surface. The modified medium tack acrylic adhesive can be peeled off without any residues, even after a long application time.

POLI-Mask 2605 can be cut on all CAD/CAM plotters. For transferring the stencil we recommend PT 190 as an Application Tape.

Universally used for all sandblast applications including stone, marble, glass or plastics. The product performs with a high rebound elasticity which shows excellent contour sharpness.

During application the following conditions are taken into consideration:

Injector-technology
Range of pressure: 2-8 bar
Granulation: 150-250 μ

Pressure beam-technology
Range of pressure: 0,5-3,0 bar
Granulation: 150-250 μ

Only mineral abrasives such as dross, quartz sand, korund or glass-pearls should be used. Abrasives like steel shot or gift shot are not suitable.

Technical Data

Carrier:	PVC film, blue, matt
Adhesive:	Acrylic
Liner:	Silicon paper (120g/m ²)
Adhesion [N/cm]:	1,60 +/- 10 %
Thickness [mm]:	0,35 +/- 5 %

Standard Dimensions

1.220 mm x 20 m

Safety Datasheet

MSDS have not been prepared for these products, they are not subject to the MSDS requirements of the Occupational Safety and Health Administrations Hazard Communication Standard, 29 C.F.R.1910.1200 (b)(6)(v).

When used under reasonable conditions and in accordance with the Poli-Tape directions for use, these products do not present a health and safety hazard. However, use or processing of the products in a manner which is not in accordance with the directions for use may affect their performance and present potential health and safety hazards.